

Page 1/15 Printing date 24.04.2020 Revision: 26.03.2020 Version number 18

Safety data sheet according to 1907/2006/EC, Article 31

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: BODY SPECIAL SPRAY

• Article number: 211

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

• Environmental release category ERC2 Formulation into mixture

· Article category AC1 Vehicles

Application of the substance / the mixture

Coating compound/ Surface coating/ paint Surface protection Special spray paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

HB BODY S.A. B' ENTRANCE BLOCK 50 DA9 & MB6 Str THESSALONIKI INDUSTRIAL AREA 57.022, SINDOS THESSALONIKI,GREECE Ph: +30 2310 790 000 Fax: +30 2310 790 033 www.hbbody.com email: hbbody@hbbody.com

Further information obtainable from:

HB BODY S.A. B' ENTRANCE BLOCK 50 DA9 & MB6 Str THESSALONIKI INDUSTRIAL AREA 57.022, SINDOS THESSALONIKI,GREECE Ph: +30 2310 790 000 Fax: +30 2310 790 033 www.hbbody.com email: hbbody@hbbody.com

1.4 Emergency telephone number:

Regional Medicines and Poisons Information Centre NI Pharmacy Department, Royal Hospital Suite Grosvenor Road Belfast Telephone: +44 28 90 63 2032 Page 2/15 Printing date 24.04.2020 Revision: 26.03.2020 Version number 18

(Contd. of page 1)

Fax: +44 28 90 24 80 30 Emergency telephone: 844 892 0111 E-mail address: nirdic.nirdic@belfasttrust.hscni.net

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS02 flame



H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Repr. 2	H361d	Suspected of damaging the unborn child.
STOT RE 2	H373	May cause damage to the central nervous system through prolonged or repeated exposure.
· · · · · · · · · · · ·		



Skin Irrit. 2H315Causes skin irritation.Aquatic Chronic 3 H412Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Danger

Hazard-determining components of labelling:

toluene

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- H315 Causes skin irritation.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to the central nervous system through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- P251 Do not pierce or burn, even after use.
- P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

*

Trade name: BODY SPECIAL SPRAY

		(Contd. of page 2)
	e. May produce an allergic reaction. ssible without sufficient ventilation.	
Results of PBT and vPvB	assessment	
 • PBT: Not applicable. • vPvB: Not applicable. 		
SECTION 3: Composition/info	-	
• 3.2 Chemical characterisat • Description: Mixture of hazar		
· Dangerous components:		
CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3 RTECS: XS 5250000 Reg.nr.: 01-2119471310-51-0003 01-2119471310-51-0003 01-2119471310-51-0005		35-<40%
01-2119471310-51-0002 01-2119471310-51-0027 CAS: 106-97-8 EINECS: 203-448-7	butane, pure lam. Gas 1, H220	30-<35%
Index number: 601-004-00-0 RTECS: EJ 4200000	Acute Tox. 3, H331 Press. Gas (Comp.), H280	
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 RTECS: ZE 2100000 Reg.nr.: 01-2119488216-32-001 01-2119488216-32-002 01-2119488216-32-003	xylene Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 RTECS: TZ 4300000	isobutane Flam. Gas 1, H220 Press. Gas (Comp.), H280	2.5-<5%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35-0001	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H332; STOT SE 3, H335-H336	2.5-<5%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 RTECS: TX 2275000	propane Flam. Gas 1, H220 Press. Gas (Comp.), H280	2.5-<5%
		(Contd. on nage /J)

(Contd. on page 4) GB

CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-001-00-6 RTECS: BD 0330000	(Co Aluminium Pyr. Sol. 1, H250; Water-react. 2, H261	ntd. of page 3) <2.5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 RTECS: NT 8050000 Reg.nr.: 01-2119457558-25-000 01-2119457558-25-000		<2.5%
CAS: 141-32-2 EINECS: 205-480-7 Index number: 607-062-00-3 RTECS: UD 3150000	n-butyl acrylate Flam. Liq. 3, H226 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens H317; STOT SE 3, H335	≥0.1-<1% . 1,
Additional information:	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation: In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

In case of skin contact DO NOT clean effected area with solvents or thinners. Take off all contaminated clothing at once. Wash skin thoroughly with neutral pH soap and water. In any suspicion that skin irritation persists call a doctor.

• After eye contact: Rinse opened eye for several minutes under running water.

• **After swallowing:** If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• 5.2 Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced. • 5.3 Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

Speial protective equipment and fire fighting procedures:

Mouth respiratory protective device.

Firefighter's should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Trade name: BODY SPECIAL SPRAY

(Contd. of page 4)

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

•7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm Sk

106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

> (Contd. on page 6) GB

Trade name: BODY SPECIAL SPRAY

(Contd. of page 5)

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

141-32-2 n-butyl acrylate

WEL Short-term value: 26 mg/m³, 5 ppm Long-term value: 5 mg/m³, 1 ppm

Regulatory information WEL: EH40/2020

Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift

Parameter: methyl hippuric acid

• Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the baseis of the different substances in the preparation.

For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)

• For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves

(Contd. on page 7) _{GB} Page 7/15 Printing date 24.04.2020 Revision: 26.03.2020 Version number 18

Trade name: BODY SPECIAL SPRAY

• **Eye protection:** Safety glasses



*

Tightly sealed goggles

• Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

(Contd. of page 6)

Safety data sheet

SECTION 9: Physical and chemical propertie	
9.1 Information on basic physical and ch	iemical properties
General Information	
· Appearance: Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
· Odour threshold:	Not determined.
pH-value:	Not determined.
[·] Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	-44.5 °C
· Flash point:	< 0 °C
Flammability (solid, gas):	Not applicable.
Autoignition temperature:	365 °C
 Decomposition temperature: 	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
• Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.5 Vol %
Vapour pressure at 20 °C:	2 hPa
Density at 20 °C:	0.61107 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with water:	Fully minimula
	Fully miscible.
Partition coefficient: n-octanol/water	🕻 Not determined.
Viscosity:	N
Dynamic: Kinematic:	Not determined. Not determined.
Solvent content:	NUL delet Hillied.
Organic solvents:	84.6 %
organic solvenics.	04.0 /0

(Contd. of page 7)

```
VOC (EC)
  Solids content (volume):
<sup>•</sup> 9.2 Other information
```

540.7 g/l 11.6 % No further relevant information available.

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal LD50 32,498 mg/kg Inhalative LC50/4 h >116 mg/l 108-88-3 toluene Oral LD50 5,000 mg/kg (rat) Dermal LD50 (static) 12,124 mg/kg (rabbit) Inhalative LC50/4 h 5,320 mg/l (mouse) 106-97-8 butane, pure Inhalative LC50/4 h 658 mg/l (rat)

1330-20-7 xvlene

Oral

Oral LD50 4,300 mg/kg (rat) Dermal LD50 2,000 mg/kg (rabbit) Inhalative LC50/4 h 11 mg/l (ATE)

64742-95-6 Solvent naphtha (petroleum), light arom.

LD50 >6,800 mg/kg (rat) Dermal | D50 >3,400 mg/kg (rab) Inhalative LC50/4 h >10.2 mg/l (rat)

67-63-0 propan-2-ol

Oral LD50 5,045 mg/kg (rat) Dermal LD50 12,800 mg/kg (rabbit)

Inhalative LC50/4 h 30 mg/l (rat)

141-32-2 n-butyl acrylate

Oral LD50 900 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Page 9/15 Printing date 24.04.2020 Revision: 26.03.2020 Version number 18

Trade name: BODY SPECIAL SPRAY

(Contd. of page 8)

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
- Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to the central nervous system through prolonged or repeated exposure.

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

12.2 Persistence and degradability

This prouduct contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

• **Remark:** Harmful to fish

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

• **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT).

• **vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

HP3 Flammable

HP4 Irritant - skin irritation and eye damage

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP10 Toxic for reproduction

HP14 Ecotoxic

(Contd. on page 10) GB Page 10/15 Printing date 24.04.2020 Revision: 26.03.2020 Version number 18

Trade name: BODY SPECIAL SPRAY

(Contd. of page 9) Uncleaned packaging: • **Recommendation:** Disposal must be made according to official regulations. • **Recommended cleansing agents:** Water, if necessary together with cleansing agents. **SECTION 14: Transport information** · 14.1 UN-Number ADR, IMDG, IATA UN1950 · 14.2 UN proper shipping name · ADR UN1950 AFROSOLS AEROSOLS AEROSOLS, flammable · 14.3 Transport hazard class(es) ADR · Class 2 5F Gases. · Label 2.1 IMDG, IATA · Class 2.1 · Label 2.1 · 14.4 Packing group ADR, IMDG, IATA Void 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): **EMS Number:** F-D.S-U Stowage Code SW1 Protected from sources of heat. SW2 Clear of living quarters. Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

Page 11/15 Printing date 24.04.2020 Revision: 26.03.2020 Version number 18

Trade name: BODY SPECIAL SPRAY

(Contd. of page 10)

Transport/Additional information:	
ADR	
· Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
· Limited quantities (LQ)	1L
• Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture None of the ingredients is listed.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



Signal word Danger

Hazard-determining components of labelling:

toluene

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- H315 Causes skin irritation.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to the central nervous system through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU

• Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48

Trade name: BODY SPECIAL SPRAY

(Contd. of page 11)

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H250 Catches fire spontaneously if exposed to air.
- H261 In contact with water releases flammable gases.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to the central nervous system through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: Department of Quality Control

Contact:

HB BODY S.A

- Ms Olympia Stamkou Ph: +30 2310 790 032
- fax: +30 2310 790 032

email: stamkou@hbbody.com

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1: Flammable gases Category 1
- Aerosol 1: Aerosols Category 1
- Press. Gas (Comp.): Gases under pressure Compressed gas
- Flam. Liq. 2: Flammable liquids Category 2
- Flam. Liq. 3: Flammable liquids Category 3
- Pyr. Sol. 1: Pyrophoric solids Category 1
- Water-react. 2: Substances and mixtures which in contact with water emit flammable gases Category 2
- Acute Tox. 4: Acute toxicity dermal Category 4
- Acute Tox. 3: Acute toxicity inhalation Category 3

Page 13/15 Printing date 24.04.2020 Revision: 26.03.2020 Version number 18

(Contd. of page 12)

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 • *** Data compared to the previous version altered.**

> GB (Contd. on page 14)

(Contd. of page 13)

Annex: Exposure scenario Short title of the exposure scenario Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites • Product category PC9a Coatings and paints, thinners, paint removers * Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities · Article category AC1 Vehicles • Environmental release category ERC2 Formulation into mixture Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet. **Conditions of use** According to directions for use. **Duration and frequency** Frequency of use: · Physical parameters The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation. Physical state Aerosol Concentration of the substance in the mixture The substance is main component. Other operational conditions Other operational conditions affecting environmental exposure No special measures required. Use only on hard ground. Other operational conditions affecting worker exposure Avoid contact with the skin. Do not breathe aerosol. Take precautionary measures against static discharge. Keep away from sources of ignition - No smoking. Avoid long-term or repeated skin contact. Other operational conditions affecting consumer exposure No special measures required. Keep out of the reach of children. Other operational conditions affecting consumer exposure during the use of the product Not applicable. Risk management measures • Worker protection [•] Organisational protective measures Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

• Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Use product only in enclosed systems.

Personal protective measures

Avoid contact with the skin.

Pregnant women should strictly avoid inhalation or skin contact.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Page 15/15 Printing date 24.04.2020 Revision: 26.03.2020 Version number 18

Trade name: BODY SPECIAL SPRAY

(Contd. of page 14)

Keep locked up and out of the reach of children.

Environmental protection measures

· Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point. Do not allow to reach sewage system.

· Soil

The product is only processed over the concrete collecting basin.

Prevent contamination of soil.

• **Disposal measures** Ensure that waste is collected and contained.

• **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste type Partially emptied and uncleaned packaging

Exposure estimation

• **Consumer** This product is to be used by professional technitians only.

• Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.